

IQUBE

IQRF gateway IQD-GW-01A

Description

IQUBE is an indoor gateway for the IQRF platform. It is intended to host the Coordinator of IQMESH wireless network.

Key features

- Based on [Orange Pi Zero](#) and Linux open-source [IQRF Gateway Daemon](#)
- Connectable to Internet and optionally to any existing cloud servers (e.g. IBM Cloud, Microsoft Azure, AWS IoT, Hexio IoT)
- Multiple communication channels UDP, MQ, MQTT and WebSocket
- Management through the [IQRF Gateway Webapp](#)



Purpose

- The easiest implementation of IQRF network Coordinator and the gateway with Internet /LAN connectivity enabling to control and manage wireless end devices.

Applications

- IQRF wireless Mesh (IQMESH) networks
- For both (STD as well as STD+LP) network types
- IQRF interoperable as well as non-interoperable applications
- Internet of Things

Technical specifications

Typical values (until otherwise specified)

Power supply	5 V DC, 2 A max. Connected via microUSB cable.
RF transceiver	TR-76D, DPA-Coordinator-UART plug-in uploaded
RF band	868 MHz or 916 MHz, configurable
RF range	Tens of meters in buildings (depends on the environment and obstacles) Up to 400 m in free space
Other RF parameters	See TR-76D datasheet
CPU	Allwinner H2 ARM Cortex A7 Quad-core
SD card memory	8 GB
Interfaces	USB 2.0, Ethernet 100 Mb/s
Custom DPA Handler	HWPID = 3004
Ambient temperature	-10 °C to +40 °C
Relative humidity	0% to 90% (without hoar-frost and condensation)
Size	50 mm x 54 mm x 36 mm
Weight	60 g

More information at docs.iqrf.org/iqd-gw-01.